

# **TECHNICAL DATA SHEET**

8/1.2mm × 165mm Hybrid Engineered Wood Flooring

#### **BOARD PROFILE:**



1.2mm Wood Top Layer

5.5mm SMART Core

1.5mm Acoustic Back

## Random Length Boards

Width 165mm

600mm to 1200mm

#### **PRODUCT DIMENSIONS & HANDLING:**

Board Depth:	8mm	Box Size:	2m²
Board Width:	165mm	Box Weight:	24.2kg
Board Length:	600mm to 1200mm	Pieces per Box:	10

### **BOARD DETAIL:**

Type of Board:	Hybrid Enginnered Wood Flooring		Fix System:	Unilin Click System	
Finish:	UV Lacquered	5% Matt	Grade:	Prime	
Wood Surace:	Wired Brush		Janka Reading:	1375 Based on ASTM D1037 Test	
Bevel Detail:	5mm micro beveled		Core Material:	Smart Core Technology	

### **MANUFACTURER TESTING:**

Indentation Tolerance :	ASTMF1914-18	Resistance to Abrasion :	ASTM D4060 : 1000mg/1000r	
Impact Test on Material :	ASTMF1265-03A : No Break	Cycled Exposure Test :	ASTM3459 : No Delaminaton	
Heat Stability:	ASTMF1514-03: 1.48%	Green Guard Certified	Compliant	
Dimension Stability Test:	ASTMF2199-18 - MD - 0.182%	Deflection Test:	ASTM1304-18: 7.0mm	

# **MISC ITEMS:**

Warranty:	10 Years - Residential					
Oak Origin:	Europe		Manufactured In:		P.R.C	
Installation:	✓	Float	✓	Bond	×	Nail
Under Floor Heating:	Suitable for UFH if installed as floating floor with DPM underlay Manifold temp must not exceed 26°C					

## **ACCREDITATIONS:**







Anzio Wood Distributed by:-